



GILLETTE GENERATORS

LEADER IN **BRUSHLESS** TECHNOLOGY

MODEL GPN-150EC

60 HERTZ

Heavy Duty, long lasting portable power for contractor and rental use. If you want clean, dependable emergency electric power, with the most reliable engines, then **GEN-PRO** is the right choice for you. These generator sets are made for the tough jobs where you need the reliability, and that good clean emergency power will be there, when you need it. This is exactly what you get, when you choose **GEN-PRO**, because of it's many heavy duty & exclusive features.



GENERATOR MODEL	GPN-150EC
MAX. KW @ 1 PH.	15.0
PRIME KW @ 1 PH.	13.5
PRIME AMPS @ 120 V.	112
PRIME AMPS @ 240 V.	56
MAX. KVA @ 3 PH. .8 P.F.	18.75
PRIME KVA @ 3 PH. .8 P.F.	17.0
PRIME KW @ 3 PH. .8 P.F.	13.5
PRIME AMPS @ 208 V. 3Ø	47.0
PRIME AMPS @ 240 V. 3Ø	40.5
PRIME AMPS @ 480 V. 3Ø	20.5
GENERATOR REGULATION	5 % VOLTAGE REGULATION ON SINGLE PHASE GEN-SETS.
FREQUENCY REGULATION	5 %, (3 HERTZ) FREQUENCY REGULATION FROM NAME PLATE RATING
"KLEEN-POWER"™	WAVEFORM DISTORTION IS LIMITED TO JUST 7 % ON ALL GEN- PRO GENERATOR SETS
ENGINE	KOHLER O.H.V.
ENGINE START METHOD	ELECTRIC
ENGINE HP/ 3600 RPM	25
ENG. CU. CENTIMETER	725
ENGINE CYLINDERS	2
LOW OIL PROTECTION	STANDARD ENGINE SHUTDOWN PROTECTION
db(A) AT 7 METERS	88
ENGINE FUEL TANK	8 GAL. (30 L.) CROSSLINK POLYETHYLENE TANK
3/4 LOAD RUN TIME (HRS)	5.0
FUEL USE, GAL/HOUR	1.6
FUEL USE, LITER/HOUR	6.06
ENGINE OIL SYSTEM	FULL PRESSURE SYSTEM W/ SPIN-ON OIL FILTER
ELECTRIC START POWER	5 HP
BUILT-IN 2-WHEEL DOLLY	YES
MAINLINE CB	(1) 50 AMP 2 POLE MAGNETIC, (1) 30 AMP PUSH BUTTON, & (2) 25 AMP PUSH BUTTON
VOLTMETER - HOUR METER	VOLTMETER AND HOUR METER (RUN TIME METER) IS INSTALLED
120 VOLT RECEPTACLE	(4) NEMA 5-15R 120 VOLT, 20 AMP RECEPTACLES WITH GFCI GROUND FAULT (1) NEMA L5-30R
240 VOLT RECEPTACLE	(1) NEMA 14-60R
LENGTH, INCHES	37
WIDTH, INCHES	26
HEIGHT, INCHES	29
SHIP WEIGHT, LBS.	357
CU. FEET SHIP BOX	22