

## Industrial Power Washers

## Power Washers



**3000 psi** - Model 006228-0 (50-State & Canada)  
UPC: 696471062281

**3500 psi** - Model 006229-0 (50-State & Canada)  
UPC: 696471062298

**4000 psi** - Model 006230-0 (50-State & Canada)  
UPC: 696471062304



## FEATURES

### POWERFUL SUBARU ENGINE

- Features low oil shutdown to protect the engine.

### PROFESSIONAL-GRADE TRIPLEX PUMP

- Ceramic pistons mean long life.

### PROFESSIONAL-GRADE SPRAY GUN

- Adjustable side handle provides precise control.
- Cushion grip and easy-to-pull trigger reduce fatigue and improve comfort.

### PRESSURE CONTROL VALVE

- Provides complete control of water pressure for all applications.

### QUICK-CLICK™ NOZZLE TIPS

- Four included, for tackling any job.

### USER FRIENDLY CONTROLS

- All in a single location, including on/off, choke, and fuel shutoff.

### NON-MARRING, STEEL-REINFORCED RUBBER HOSE

- Will not leave scuff marks on surfaces.
- Quick connectors make hose connections a snap.

### DURABLE HEAVY DUTY STYLE FRAME

- Protects the engine and pump.
- Front grab bar makes it easier to lift.

**3000 • 3500 • 4000 psi**
**specifications**
**PRESSURE AND FLOW**

Outlet Pressure (psi/bar)	3000/207 - 006228-0 3500/241 - 006229-0 4000/276 - 006230-0
Flow Rate (gpm)/(L/min)	3.0/11.4 - 3000 psi 3.7/14 - 3500 psi 3.4/12.9 - 4000 psi

**ENGINE**

Manufacturer	Subaru
Displacement (in <sup>3</sup> /cc)	16.2/265 - 3000 psi 24.7/404 - 3500 & 4000 psi
Type	OHV (Overhead Valve)
Orientation	Horizontal
Low Oil Shutdown System	Yes
Fuel Capacity (gal/L)	1.5/5.7 - 3000 psi 1.8/6.8 - 3500 & 4000 psi
Fuel On/Off Switch	Yes
Oil Capacity (oz/L)	33.8/1 - 3000 psi 40.6/1.2 - 3500 & 4000 psi
Recommended Engine Oil	SAE 30 or 10W30
Throttle Control	Manual
Choke	Manual
Starting Method	Manual

**PUMP**

Type	Belt-driven triplex
Plunger	Ceramic-coated stainless steel
Material	Aluminum body, brass head
Maximum Water Supply Temperature (°F/°C)	100/38

**HOSE**

Length (ft/m)	50/15.2
Diameter (in/mm)	.38/9.5
Rating (psi/bar)	4000/276
Connectors	Quick change

**DETERGENT SYSTEM**

Number of Chemical Tanks per Unit	0
Chemical Tank Description	None

**NOZZLES**

Number of Nozzles per Unit	4
Nozzle Descriptions	0, 15, 25, 40

**GUN & LANCE**

Gun	Professional with adjustable side handle
Gun to Lance Connection	M22 threaded
Gun to Hose Connection	Quick change
Lance Length (in/cm)	20/50.8 - 3000 psi 33/83.8 - 3500 & 4000 psi
Lance to Nozzle Connection	Quick change
Lance Material	Stainless Steel
Lance Connector Material	Brass

**FRAME & MISC.**

Handle	Fixed
Frame Construction	Welded steel
Wheels (in/cm)	5 x 13/12.7 x 33 never flat

**DIMENSIONS & WEIGHTS**

Length (in/cm)	39.5/100.3
Width (wheel to wheel, in/cm)	28.5/72.4
Height (in/cm)	26/66
Weight Including Hose, Gun & Lance (lb/kg)	178/80.7 - 3000 psi 191/86.6 - 3500 & 4000 psi
Boxed Weight (lb/kg)	232/105.2 - 3100 psi 245/111.1 - 3500 & 4000 psi
Boxed Length (in/cm)	48.5/123.2
Boxed Width (in/cm)	31/78.7
Boxed Height (in/cm)	36/91.4

**WARRANTY**

Warranty	5 year limited
----------	----------------